

Sam Bossley
Associate Marketing Manager – EMS

3800 E. Centre Ave.
Portage, MI 49002
t: 269 389 6628
sam.bossley@stryker.com

stryker[®]

Medical

Date: January, 2017

Re: Power-PRO XT Ambulance Cot Sole Source Information

To Whom It May Concern,

Stryker Medical certifies that we are the sole manufacturer of the Stryker EMS Power-PRO XT (Model 6506). This correspondence is to inform you of the unique characteristics of the Power-PRO XT Ambulance Cot. These characteristics can be broken down into two primary categories: Independent Qualification, and Ease of Use and Maintenance.

Independent Qualification

- IPX6: The system is rated to withstand powerful water jets.
- IEC 60601-1 and IEC 60601-1-2: This certification indicates that Power-PRO conforms to industry standards for mechanical and electrical safety for medical electrical devices, as well as electromagnetic compatibility and immunity.
- BS EN-1789 clause 4.5.9: This is a European dynamic crash test which subjects a 50th percentile dummy to a nominal 10g deceleration for a minimum of 50ms. Following the test there shall be no sharp edges or danger to the safety of persons in the road ambulance.¹

Ease of Use and Maintenance

- The cot has a weight capacity of 700lbs.
- When unloading with the manual release handle, the cot utilizes hydraulic dampening. Thus, the cot will not abruptly jar the operator or the patient.
- The battery is placed at the foot-end of the stretcher.
- The cot legs power-retract in 2.4 seconds which speeds load times.
- The cot provides the highest possible load height of any cot on the market at 36” and is operator adjustable to match the deck height of individual ambulances.
- The foot-end of the cot provides lifting bars and operator controls at two different heights, thus providing optimum ergonomics to most operator heights.
- The foot-end of the cot contains a large battery indicator light which displays amber or green which indicates battery level. A warning is given by a flashing amber light, providing the operator the time to change the battery before full depletion of power.
- The Model 6506 has 6” x 2” sealed bearing casters – the largest in the industry.
- The cot features a foot-end-mounted hourly usage meter. This is an easy tool to determine the timing of preventative maintenance checks.

¹ Only conforms when used with Power-LOAD (model 6390).

- The cot features powder-coating of the entire aluminum frame (including the patient handling surfaces), thus eliminating aluminum oxidation throughout the cot.
- All caster bearings are sealed, eliminating timely and costly lubrication.
- The cot is power-washable.

Please forward any further questions to your Stryker sales representative.

Sincerely,

A handwritten signature in black ink, appearing to read 'Sam Bossley', with a stylized flourish at the end.

Sam Bossley